



PETRONAS

TECHNICAL CHARACTERISTICS

TUTELA TRANSMISSION MULTIAXLE

PRODUCT CODE: 1439

APPLICATION

Synthetic Transmission Oil. Specifically formulated to satisfy the most severe needs of moder Gearboxes and Hypoid Differentials.

SPECIFICATIONS

SAE 75W-85, API GL 5, FIAT 9.55550-DA3 C.T.R.N°F426.E06

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B&C
COLOUR	--	--	GREEN or BROWN (LIGHT)
DENSITY AT 15°C	ASTM D4052	g/cm ³	0.867
VISCOSITY AT 100°C	ASTM D445	cSt	11.5
VISCOSITY AT 40°C	ASTM D445	cSt	72
VISCOSITY INDEX	ASTM D2270	--	160
VISCOSITY AT -40°C	ASTM D2983	cPs	38000
POUR POINT	ASTM D97	°C	<-45
FLASH POINT CI. O. C.	ASTM D92	°C	230
FOAM AT 24°C	ASTM D892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

09/2017